



CW NPT TYPE BRASS CABLE GLAND

Specification:

Size	20 mm to 90 mm S & L
Standard	EN 50262 : 1999
Application	For indoor or outdoor use with all types of SWA Cable
Function	Provide for Environmental Seal in the Cable Outer Sheath. Also provide mechanical cable retention & electrical continuity.
Material	Brass BS 2874 CZ121 Pb3, CW614n, CW617n
Optional Threads	METRIC, NPT, BSP, PG or as specified
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified
Operating Temp.	Standard seals -200 to +800 C
Accessories	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tags, Reducers, Adaptors, etc. as per the requirement



Technical Data:

Size	Thread Size 'C'		Minimum Length of Thread 'D'	Cable Range	
	MM	THREAD NPT		MAX 'A'	MAX 'B'
CWNPT 20S	20	1/2"	10	11.80	17.80
CWNPT 20L	20	1/2"	10	14.00	20.80
CWNPT 25S	25	3/4"	10	18.00	24.00
CWNPT 25L	25	3/4"	10	20.30	27.40
CWNPT 32S	32	1"	10	24.50	31.00
CWNPT 32L	32	1"	10	26.50	34.20
CWNPT 40S	40	1.1/4"	13	30.40	38.50
CWNPT 40L	40	1.1/4"	13	33.20	41.00



Size	Thread Size 'C'		Minimum Length of Thread 'D'	Cable Range	
	MM	THREAD NPT		MAX 'A'	MAX 'B'
CWNPT 50S	50	1.1/2"	13	40.00	47.00
CWNPT 50L	50	1.1/2"	13	44.00	53.50
CWNPT 63S	63	2"	14	50.00	59.00
CWNPT 63L	63	2"	13.50	56.00	66.00
CWNPT 75S	75	2.1/2"	15	63.50	73.00
CWNPT 75L	75	2.1/2"	15	69.00	79.00

Also available in Kit Packaging and also as per the specification.